







Qurina

Description and features

Application

Physical constant

Tools

Storage

Health & Safety

Decorative paint, Gold , high-quality, easy to use, designed to give an attractive velvety qurina forms with overlapping colors, characterized by good stability colors and gluing power, made from the finest acrylic in the world, used for the final interior layers on concrete, cement and gypsum.

- 1 All surfaces should be flat, clean and completely dry to be painted.
- 2 Apply one coat alzawaq insulator Almadina misurata
- 3 Apply two or three coats with "Almadina Misurata Putty" lengthwise and sideways", use sanding paper and then clean the dust.
- 4 Apply preparation coat of Al Madina Misurata "Latex Plus Matt".
- 5 Apply coat or two of the desired color of Al Madina Misurata "Latex Matt".
- 6 Apply coat of Al Madina Misurata "Qurina "diagonally or horizontally or randomly depends on desired form using Qurina special brush .

Color (Gold) By colors catalog

Specific gravity $1.18 \pm 0.03 \text{ Kg/l}$ Viscosity 15:20 gm/cm3

spreading rate 10:12 m2/ kilo depends on the desired form, surface thickness of the layer and

the kind of surface

PН 8 . 9

Dilution Ready for use without dilution

Dry to touch 15:20 minutes Completely dry 8 hours Hardness 24 hours Packing 1 kg - 3 kg



Trowels



sponge

Product should be stored in the original package for 12 months from the production date, store it under normal conditions and keep it away from direct sunlight.

- 1 Don't keep food in the empty package.
- 2 Keep it away from the reach of children.
- 3 Avoid direct contact with eyes or skin, in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice.
- 4 This product is free of polluted materials to the environment.

Libya - Misurata - Industrial Zone - Alaswak

Marketing: 00218918000047 marketing@almadinamisurata.com

Sales:

00218912125435







