



دهانات المدينة مسurate

Almadina Misurata Paints | AMP®



Lady Glaze

Description and features

High Quality Alkyd decorative paint, Designed to give multiple and attractive decorative forms, it has an enough Drying Time to do the suitable Design.

Using as a finally coat for interior surfaces including cement, concrete, wood, iron, and gypsum surfaces.

Application

- 1 - The surfaces should be flat, clean and completely dry.
- 2 - Apply one coat alzawaq insulator Almadina misurata
- 3 - Apply two or three coats of (Almadina Misurata Putty) with lengthwise and widthwise, sand it and clean the dust.
- 4 - Apply one coat of (Matt Alkyd paint Almadina misurata).
- 5 - Apply one coat of (Gloss Alkyd paint Almadina misurata).
- 6 - Apply one coat of (Lady glaze Almadina misurata) according to the required design by suitable forming tools.

Physical constant

Color	transparent, the coloring is done by computer
Viscosity	100 ± 5 krebs
Specific gravity	0.8 kg/liter
Thinner	kerosene
Weight	1 kg - 0.5 kg

Tools



Brush



Roller



Spray gun



sponge

Storage

Product should be stored in the original package for 24 months from the production date , store it under normal conditions and keep it away from direct sunlight.

Health & Safety

- 1 - Don't keep food in the empty package.
- 2 - Keep it away from the reach of children.
- 3 - Avoid direct contact with eyes or skin , in case of contact with eyes you should clean immediately with plenty of clean cold water and seek medical advice .
- 4 - This product is free of polluted materials to the environment.

Libya – Misurata – Industrial Zone – Alaswak

Marketing : ☎ 00218918000047 ✉ marketing@almadinamisurata.com

Sales : ☎ 00218912125435

Facebook icon amppaints1

YouTube icon amppaints

www.amp.ly

Twitter icon amppaints

Instagram icon amppaints